

-25°C DEEP FREEZER



Quality, Management, Environment, Health & Safety Standards





INTRODUCTION

MarkEn Deep Freezers set the gold standard for safe, reliable, and efficient storage of the most sensitive biological materials, including stem cells, plasma, semen, viruses, bone grafts, and other vital samples. Designed to meet the rigorous demands of life science research institutes, hospitals, blood banks, pharmaceutical and biotech companies, and industrial applications, MarkEn freezers deliver performance you can trust.

TECHNICAL EXCELLENCE

€	Wide Temperature Range: Offering precise cooling from -15°C to -25°C
(Tropical Climate Adaptation: Engineered to maintain peak performance even in high- temperature environments.
(KE)	Heavy-Duty Weight Capacity: Uniformly distributed load-bearing trays for maximum efficiency.
**	Advanced Freezing Technology: Compression cycle system ensuring rapid, frost-free freezing.
2	Eco-Conscious Design: 100 % CFC-free refrigeration and insulation for a greener planet.
	Premium-Grade Tubing: Constructed with 99.97% pure copper for superior durability and efficiency.

CUTTING-EDGE FEATURES

	Anti-Condensation Innovation: Hot line at the cabinet mouth prevents moisture buildup, safeguarding stored samples.
€ *	Intelligent Data Management: Internal memory captures temperature and alarm records, easily transferable to a PC.
<u>ــــــــــــــــــــــــــــــــــــ</u>	Effortless Defrosting: Convenient defrosting provision simplifies maintenance.
	Auto Door Closure: Ensures consistent internal temperatures by preventing accidental exposure.
Ø	Unmatched Longevity: Designed for a minimum 10-year lifespan with guaranteed spare parts availability.



RIGOROUS SAFETY AND CERTIFICATIONS




ESSENTIAL ACCESSORIES



Precision Stem Alcohol Thermometer: Delivers accurate temperature monitoring for optimal sample preservation.



Advanced Voltage Stabilizer: Servo-controlled with automatic high-low voltage cut-off and time delay restart, ensuring uninterrupted performance.





- -

n	2
υ	э

TECHNICAL SPECIFICATIONS		
Make	MarkEn	
Type of Cabinet	Vertical/Upright	
Color	White	
Outer Material of Cabinet	Corrosion resistance CRCA/GI powder coated steel (18swg)	
Inner Material of Cabinet	Stainless Steel 304	
PUFF Insulation- CFC free	Cabinet: 127 mm	
	Door : 115 mm	
Ground Clearance	100 mm with 4 castor wheels (2 Lockable and 2 un-lockable)	
Door	Solid door with Lock-Key and handle and 04 Nos Inner Door and includes standard key lock and provision for padlock.	
Inner Shelves	04 Nos	
Compressor	Hermetically sealed compressor	
Refrigerants	CFC-HCFC-Free non flammable refrigerants. R452A	
Condensing	Skin condensing Inner and air cooled grooved aluminum fins OR forced air circulation to maintain.	
Pull down time	04 Hours	
Temperature uniformity	±3°C or Less	
Environmental Condition	Maximum +45°C with Humidity 5% to 95% RH	
Control System	Fully programmable microprocessor controlled with membrane keypad and Password Protected eye level control panel	
Temperature Monitoring System	With IOT (Cloud Manage) supported (Optional) and 7 days inkless Chart Recorder (Optional).	
Display	Digital Temperature Display 7" Touch Screen.	
Alarms	Audible and visual alarm system for over and under temperature, sudden power failure, system failure, Clogged Condenser Filter , Door open and battery low.	
Battery Backup	74 Hrs Battery Backup for Digital Display, Total Alarm system, Temp. recording system with auto recharging facility.	
Access port	Provision of connecting LN2/CO2 Backup system for maintaining the set temperature during power failure.	
Noise level	<55 db	
Power Consumption rate-	Stable Running: 2.040 kWh/24Hrs Cool Down Test:2.30kWh/24Hrs.	
Power supply	Suitable for Input Voltage Range 100 to 290 VAC, 50 Hz +10%	

CERTIFICATIONS

Quality, Management, Environment, Health & Safety Standards





ALL-IN-ONE SOLUTION FOR

Cold Chain Solution Medical Equipment Blood Bank Equipment Hospital & Scientific Equipment Hospital Furniture & Infrastructure Commercial Refrigeration







Service center



Committed Engineers



OUR ESTEEMED CUSTOMERS





Regd office & Factory: 93/1, MIDC Satpur, Nashik- 422007 (IND)
Corporate office: 410, Maker Chambers V, Nariman Point, Mumbai - 400021
New Delhi office - DLF Tower, Jasola | Chandigarh Office - CCC, VIP Road
Customer Care No.+91 91 3030 5959
www.markenworld.com info@markenworld.com



Authorized Distributor Details